

suitable reducing adapter	302150; 302155; 302160; 302165
Clamping $\varnothing D_1$	20 mm
Reach L_1	54 mm
Overhang dimension A	80 mm
External $\varnothing D$	52.5 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Machining strategy	HSC
Type of product	Hydraulic clamping chuck

Accessories

Slotted reducing adapter Clamping range $\varnothing D1$ 16 mm	302160 16
Slotted reducing adapter Clamping range $\varnothing D1$ 10 mm	302155 10
Slotted reducing adapter Clamping range $\varnothing D1$ 3 mm	302155 3
Slotted reducing adapter Clamping range $\varnothing D1$ 12 mm	302160 12
Slotted reducing adapter Clamping range $\varnothing D1$ 6 mm	302160 6
Slotted reducing adapter Clamping range $\varnothing D1$ 4 mm	302160 4
Slotted reducing adapter Clamping range $\varnothing D1$ 3 mm	302160 3
Slotted reducing adapter Clamping range $\varnothing D1$ 5 mm	302155 5
Slotted reducing adapter Clamping range $\varnothing D1$ 16 mm	302155 16
Slotted reducing adapter Clamping range $\varnothing D1$ 8 mm	302155 8
Slotted reducing adapter Clamping range $\varnothing D1$ 14 mm	302160 14

Slotted reducing adapter Clamping range Ø D1 4 mm	302155 4
Slotted reducing adapter Clamping range Ø D1 6 mm	302155 6
Slotted reducing adapter Clamping range Ø D1 10 mm	302160 10
Slotted reducing adapter Clamping range Ø D1 8 mm	302160 8
Slotted reducing adapter Clamping range Ø D1 12 mm	302155 12
Slotted reducing adapter Clamping range Ø D1 5 mm	302160 5
Slotted reducing adapter Clamping range Ø D1 14 mm	302155 14