

**Garant**
**Short drill chuck Form A, HSK-A 63, Clamping range: 0,3-10 mm**

**Order data**

Order number	307682 0,3-10
GTIN	4045197868800
Item class	31B

**Description**
**Version:**

- **For clockwise and anticlockwise rotation.**
- **With Balluffchip bore.**

With through coolant feed up to max. 50 bar.  
Concentricity  $\leq 20 \mu\text{m}$ . Concentricity  $\leq 20 \mu\text{m}$ .

**Supplied with:**

**Clamping wrench** with T-handle.

**Optional extras:**

Socket wrench No. 309890. Coolant tube No. 309880.

Type: slim

Overhang dimension A: 73 mm

External  $\varnothing$  D: 38 mm

Spare chuck key No. 627425: 4 AF

**Technical description**

Spare chuck key No. 627425	4 AF
Overhang dimension A	73 mm
Clamping range	0.3 - 10.2 mm
Type	slim
External $\varnothing$ D	38 mm

Adapter	HSK-A 63
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-7
Arbor standard	DIN 69893-1
Shape	A
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 µm
Type of product	Short drill chuck

---

## Accessories

Hexagon screwdriver with T-handle Hexagon 4 mm	627425 4
Hexagon screwdriver, with T-handle Hexagon 4 mm	627481 4