

Garant
Short drill chuck Form F, HSK-F 63, Clamping range: 0,5-16 mm

Order data

Order number	307705 0,5-16
GTIN	4045197761156
Item class	33W

Description
Version:

- For clockwise and anticlockwise rotation.
- With Balluffchip bore.

Concentricity $\leq 20 \mu\text{m}$.

Supplied with:

Clamping wrench with T-handle.

Optional extras:

Socket wrench No. 309890. Coolant tube No. 309880.

Concentricity: $\leq 20 \mu\text{m}$

Type: standard

Overhang dimension A: 102 mm

External \varnothing D: 57 mm

Spare Torx® chuck key No. 625220: TX25

Technical description

Type	standard
Spare Torx® chuck key No. 625220	TX25
Overhang dimension A	102 mm
External \varnothing D	57 mm
Adapter	HSK-F 63

Arbor standard	DIN 69893-1
Arbor standard	DIN 69882-7
Arbor standard	ISO 12164-1
Shape	F
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 μm
Type of product	Short drill chuck

Accessories

Screwdriver with T-handle short, for Torx® Torx® profile TX25	625220 TX25
Screwdriver for Torx®, short, with T-handle Torx® profile TX25	625221 TX25