



Short drill chuck Form A, HSK-A 100, Clamping range: 2,5-16 mm



Order data

Order number	307760 2,5-16
GTIN	2050001690050
Item class	33W

Description

Version:

- For clockwise and anticlockwise rotation.
- With Balluffchip bore.

Supplied with:

Clamping wrench with T-handle.

Optional extras:

Socket wrench No. 309890. Coolant tube No. 309880.

Type: standard

Overhang dimension A: 116 mm

External Ø D: 57 mm

Spare chuck key No. 627425: 6 AF

Technical description

Clamping range	2.5 - 16 mm
Type	standard
Overhang dimension A	116 mm
Spare chuck key No. 627425	6 AF
External Ø D	57 mm
Adapter	HSK-A 100
Arbor standard	ISO 12164-1

Arbor standard	DIN 69882-7
Arbor standard	DIN 69893-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 30 μm
maximum tightening torque $M_{d\max}$	≤ 14 Nm
Type of product	Short drill chuck

Accessories

Hexagon screwdriver with T-handle Hexagon 6 mm	627425 6
Hexagon screwdriver, with T-handle Hexagon 6 mm	627481 6