## Garant

Shrink-fit chuck with cooling channel bore, HSK-A 63 ultra short, Clamping range Ø D1: 20 mm



## Order data

Order number	308165 20
GTIN	4045197468697
Item class	31A

## Description

Version:

From clamping  $\emptyset$  D<sub>1</sub> 6 mm with tapped holes for balancing screws.

- · High-temperature steel.
- Size 3 5 for carbide, from size 6 for HSS and carbide.
- · With Balluffchip bores.
- **GARANT:** HSK mating faces machined. **All shanks hard turned (for smooth running!). Ultra short:** More stability and stiffness, less vibration. This ensures longer tool life and better surface quality. No length adjustment available.

With cooling channel bores tapped for plugging.

#### **Application:**

- $\cdot$  For holding end mills and drills with parallel shank to h6 tolerance.
- · Suitable for inductive, contact and hot air shrink-fit units.

#### Supplied with:

For chucks with length adjustment including a length adjustment screw (from clamping  $\emptyset$  D<sub>1</sub> 6 mm).

#### **Optional extras:**

Coolant tube No. 309880, socket wrench No. 309890, shrink-fit chuck extension No. 302410 – 302416, shrink-fit units No. 354210 – 354450, balancing screw set No. 309906 180. Cooling channel bore: lockable Overhang dimension A: 75 mm External Ø D: 43 mm Ø D<sub>2</sub>: 35 mm

# **Technical description**

ØD <sub>2</sub>	35 mm
Clamping $\emptyset$ D <sub>1</sub>	20 mm
Overhang dimension A	75 mm
External Ø D	43 mm
Cooling channel bore	lockable
Adapter	HSK-A 63 ultra short
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	А
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HPC
Machining strategy	HSC
Type of product	Shrink-fit chuck

# Accessories

Screening plate for coil SU1 for clamping Ø 20-32 mm	354240 20-32
Shrink-fit unit Type SU1	354210 SU1
Cooling unit Type CU1	354215 CU1
Cooling adapter long 4.5° for clamping Ø 16,1-22 mm	354236 16,1-22
Subframe cupboard	354290
Cooling adapter short 4.5° for clamping Ø 16,1-22 mm	354235 16,1-22
Screening plate for coil SU1 for clamping Ø 12-20 mm	354240 12-20