



## Shrink-fit chuck, HSK-A 63 short, Clamping range $\varnothing D_1$ : 12 mm



### Order data

Order number	308183 12
GTIN	2050001690128
Item class	33W

### Description

#### Version:

From clamping  $\varnothing D_1$  6 mm with tapped holes for balancing screws.

Integral length adjustment of the tool from clamping  $\varnothing D_1$  6 mm (adjustment travel 10 mm).

- **High-temperature steel.**
- **Size 3 – 5 for carbide, from size 6 for HSS and carbide.**
- **With Balluffchip bores.**

#### Application:

- **For holding end mills and drills with parallel shank to h6 tolerance.**
- **Suitable for inductive, contact and hot air shrink-fit units.**

#### Supplied with:

For chucks with length adjustment including a length adjustment screw (from clamping  $\varnothing D_1$  6 mm).

#### Optional extras:

Coolant tube No. 309880, socket wrench No. 309890, shrink-fit chuck extension No. 302410 – 302416, shrink-fit units No. 354210 – 354450, balancing screw set No. 309906 180.

Overhang dimension A: 90 mm

External  $\varnothing D$ : 32 mm

$\varnothing D_2$ : 24 mm

### Technical description

Overhang dimension A	90 mm
Clamping $\varnothing D_1$	12 mm

Ø D <sub>2</sub>	24 mm
External Ø D	32 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HPC
Machining strategy	HSC
Type of product	Shrink-fit chuck

## Accessories

Subframe cupboard	354290
Cooling unit Type CU1	354215 CU1
Cooling adapter long 4.5° for clamping Ø 9,1-12 mm	354236 9,1-12
Shrink-fit unit Type SU1	354210 SU1
Cooling adapter short 4.5° for clamping Ø 9,1-12 mm	354235 9,1-12
Screening plate for coil SU1 for clamping Ø 6-12 mm	354240 6-12