

Garant
Whistle-Notch arbor, PSC 63 short, Clamping range \varnothing D1: 16 mm

Order data

| | |
|--------------|---------------|
| Order number | 308510 16 |
| GTIN | 4045197486240 |
| Item class | 31C |

Description
Version:

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

Application:

For clamping tools with suitable clamping flat (2°) to DIN 1835 Form E and DIN 6535 Form HE (= Whistle Notch).

Optional extras:

Coolant pipe No. 309885, coolant pipe wrench No. 309893.

Machining strategy: HSC

Overhang dimension A: 80 mm

External \varnothing D: 48 mm

Technical description

| | |
|---------------------------------------|--------------|
| Clamping \varnothing D ₁ | 16 mm |
| Overhang dimension A | 80 mm |
| External \varnothing D | 48 mm |
| Adapter | PSC 63 short |
| Arbor standard | ISO 26623-2 |

| | |
|---------------------------------------|---------------------|
| Through-coolant | yes |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 3 μm |
| Machining strategy | HPC |
| Machining strategy | HSC |
| Type of product | Side lock arbor |

Accessories

| | |
|--|------------|
| Extension PSC-63 / PSC-63 A dimension 60 mm | 318896 60 |
| Reducing adapter for PSC shank PSC inner 8 | 306976 8 |
| Reducing adapter for PSC shank PSC inner 6 | 301276 6 |
| Reducing adapter for PSC shank PSC inner 6 | 306976 6 |
| Extension PSC-63 / PSC-63 A dimension 100 mm | 318896 100 |
| Reducing adapter for PSC shank PSC inner 8 | 301276 8 |