

**Garant**
**Face mill arbor with cooling channel bores, BT 63 ultra short, Spigot Ø d1: 16 mm**

**Order data**

Order number	308546 16
GTIN	4045197703675
Item class	31C

**Description**
**Version:**

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

**Application:**

For holding shell end mills and face mills with cross keyway.

**Supplied with:**

Lock screw.

**Optional extras:**

Toggle spanner No. 309840, cutter lock screw No. 309860.

Coolant tube and assembling key for coolant tubes No. 309885; 309893.

Machining strategy: HPC

Overhang dimension A: 40 mm

External Ø D: 38 mm

Spare milling cutter lock screw No. 309860 / 309861: 16

Suitable toggle spanner No. 309840: 16

**Technical description**

Suitable toggle spanner No. 309840	16
Overhang dimension A	40 mm

Spigot Ø d <sub>1</sub>	16 mm
Spare milling cutter lock screw No. 309860 / 309861	16
External Ø D	38 mm
Adapter	BT 63 ultra short
Arbor standard	ISO 26623-2
Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

---

## Accessories

Toggle spanner for mandrel Ø 16 mm	309840 16
------------------------------------	-----------