

Garant

Face mill arbor with cooling channel bores, PSC 63 A = 65, Spigot Ø d1: 27 mm


Order data

Order number	308547 27
GTIN	4045197703736
Item class	31C

Description
Version:

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

Application:

For holding shell end mills and face mills with cross keyway.

Supplied with:

Lock screw.

Optional extras:

Toggle spanner No. 309840, cutter lock screw No. 309860.

Coolant tube and assembling key for coolant tubes No. 309885; 309893.

Machining strategy: HPC

External Ø D: 60 mm

Spare milling cutter lock screw No. 309860 / 309861: 27

Suitable toggle spanner No. 309840: 27

Technical description

Suitable toggle spanner No. 309840	27
Spigot Ø d ₁	27 mm
Spare milling cutter lock screw No. 309860 / 309861	27

External Ø D	60 mm
Adapter	PSC 63 A = 65
Arbor standard	ISO 26623-2
Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel Ø 27 mm	309840 27
------------------------------------	-----------