

Garant
Face mill arbor with cooling channel bores, PSC 80 short, Spigot Ø d1: 16 mm

Order data

Order number	308551 16
GTIN	4045197870681
Item class	31C

Description
Version:

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

Application:

For holding shell end mills and face mills with cross keyway.

Supplied with:

Lock screw.

Optional extras:

Toggle spanner No. 309840, cutter lock screw No. 309860.

Coolant tube and assembling key for coolant tubes No. 309885; 309893.

Machining strategy: HPC

Overhang dimension A: 50 mm

External Ø D: 38 mm

Spare milling cutter lock screw No. 309860 / 309861: 16

Suitable toggle spanner No. 309840: 16

Technical description

Overhang dimension A	50 mm
Suitable toggle spanner No. 309840	16

External Ø D	38 mm
Spare milling cutter lock screw No. 309860 / 309861	16
Spigot Ø d ₁	16 mm
Adapter	PSC 80 short
Arbor standard	ISO 26623-2
Cooling channel bore	lockable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel Ø 16 mm	309840 16
------------------------------------	-----------