

Garant
Face mill arbor with cooling channel bores, PSC 80 short, Spigot Ø d1: 40 mm

Order data

Order number	308551 40
GTIN	4045197870728
Item class	31C

Description
Version:

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

Application:

For holding shell end mills and face mills with cross keyway.

Supplied with:

Lock screw.

Optional extras:

Toggle spanner No. 309840, cutter lock screw No. 309860.

Coolant tube and assembling key for coolant tubes No. 309885; 309893.

Machining strategy: HPC

Overhang dimension A: 60 mm

External Ø D: 88 mm

Spare milling cutter lock screw No. 309860 / 309861: 40

Suitable toggle spanner No. 309840: 40

Technical description

Spare milling cutter lock screw No. 309860 / 309861	40
Overhang dimension A	60 mm

Spigot Ø d ₁	40 mm
Suitable toggle spanner No. 309840	40
External Ø D	88 mm
Adapter	PSC 80 short
Arbor standard	ISO 26623-2
Cooling channel bore	lockable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel Ø 40 mm	309840 40
------------------------------------	-----------