

**Garant**
**Short drill chuck, PSC 63, Clamping range: 1-16 mm**

**Order data**

Order number	308595 1-16
GTIN	4045197932020
Item class	31B

**Description**
**Version:**

- **For clockwise and anticlockwise rotation.**
- **Sand-blasted.**
- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

**Supplied with:**
**Torx® clamping wrench.**
**Optional extras:**

Coolant tube No. 309885; socket No. 309893.

maximum tightening torque  $M_{d,max} \leq 14 \text{ Nm}$ 

Overhang dimension A: 93.1 mm

External  $\varnothing$  D: 50 mm

Spare Torx® chuck key No. 625220: TX25

**Technical description**

Overhang dimension A	93.1 mm
External $\varnothing$ D	50 mm
Spare Torx® chuck key No. 625220	TX25
Clamping range	1 - 16 mm
Adapter	PSC 63

Arbor standard	ISO 26623-2
Through-coolant	yes
Balance quality G at rotational speed	G 2.5 at 18,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
maximum tightening torque $M_{d \max}$	$\leq 14 \text{ Nm}$
Type of product	Short drill chuck