



Special pull stud with internal thread, with bore, suitable for steep tapers: 40



Order data

Order number	308740 40
GTIN	4045197151063
Item class	32Z

Description

Description:

The toolholder is securely pulled into the spindle by the spindle's clamping gripper using the pull stud. Pull studs come in different versions. They are an important link between the machine and tool. Stringent requirements apply for the accuracy, strength and reliability of pull studs.

Application:

For tools with taper shanks see also **DIN 69871 / ISO 7388-1**.

Note:

Sealed – with O-ring.

Look in the eShop – you will find the right clamping wrench and width for every job.

When installing the pull stud, cheque the correct tightening torque. No suitable chuck key available.

Collar Ø D: 25.1 mm

Head Ø D₁: 21.1 mm

Overall length L: 53 mm

L₁: 25.1 mm

Thread M: M16

Internal thread: M16

Technical description

Internal thread	M16
suitable for taper arbors with colour code	SK 40
Head Ø D ₁	21.1 mm

Thread M	M16
suitable for steep tapers	40
L ₁	25.1 mm
Collar Ø D	25.1 mm
Overall length L	53 mm
maximum tightening torque	50 Nm
Internal thread depth	17 mm
Width across flats	22 mm
Hole characteristics	with bore
Type of product	Pull Stud