


**FAHRION®**  
PRAZISION
**ER collet HP with seal, ER 16, Nominal clamping  $\varnothing$  d: 7 mm**

**Order data**

Order number	309371 7
GTIN	2050001767585
Item class	33F

**Description**
**Version:**

**System concentricity** and repetition accuracy **3  $\mu$ m** ( $3 \times D$ , maximum = 50 mm), in conjunction with FAHRION CENTRO P chucks.

**Corrosion protection:** Collets fully coated with FAHRION Protect, including the functional faces.

**Advantage:**

The coating increases the service life of the collet and ensures full functionality and precision.

**Suitable for :**

Precision ER collet chuck CENTRO P.

**Note:**

- **Optimum concentricity only when used in CENTRO P chucks.**
- **Clamping range h10 (nominal size only).**

With **seal** for through-coolant feed (for use up to 100 bar). **Similar to** ISO 15488-A.

Concentricity:  $\leq 2 \mu$ m

Overall length L: 27.5 mm

**Technical description**

Nominal clamping $\varnothing$ d	7 mm
Adapter	ER 16
Standard	ISO 15488-A

Concentricity	≤ 2 μm
Type	425 E
External Ø D	16.7 mm
Overall length L	27.5 mm
Type of product	Clamping head