

Garant
HSK coolant tube, for HSK: 32

Order data

| | |
|--------------|---------------|
| Order number | 309880 32 |
| GTIN | 2050001707819 |
| Item class | 39Z |

Description
Version:

Special O-ring up to 120 bar, angular movement from $\pm 1^\circ$, polished, with 2 sealing rings.

Coolant-resistant Viton® seals.

- **Fine polished surface, hardened and burnished.**
- **Two polished transition radii.**
- **Full movement thanks to two O-rings.**
- **Hardened threaded sleeves with rolled, high-compression thread flanks.**

Description:

HSK coolant pipe – a small component with a big effect! When tools are changed thousands of times per day, it is important that the interface between the coolant pipe and machine spindle seal remains clean and, above all, that it maintains process reliability.

Feature:

Special O-ring up to 120 bar, angular movement from $\pm 1^\circ$, polished.

Suitable for :

HSK tool holders.

Thread M: M10×1

Ø D: 6 mm

Overall length L: 26 mm

Technical description

| | |
|--------------------|--------|
| Ø D | 6 mm |
| suitable for arbor | HSK 32 |

| | |
|-------------------|--------------|
| Thread M | M10×1 |
| Overall length L | 26 mm |
| maximum pressure | 120 bar |
| Angular movement | ±1 degrees |
| Surface treatment | polished |
| Type of product | Coolant tube |

Accessories

| | |
|--|-----------|
| Socket wrench for coolant tubes for HSK 32 | 309890 32 |
|--|-----------|