#### SCHUNK

# Self-centring three-jaw chuck ROTA-S 2.0 with short taper and scroll stepped jaws, DIN 702-3, Type: 200/5



## Order data

| Order number | 313135 200/5  |
|--------------|---------------|
| GTIN         | 2050001928818 |
| Item class   | 33U           |

## Description

#### Version:

- · Maximum concentricity and jaw exchange repeatability.
- · Long service life with very high precision.
- · Modular protective sleeve system.
- · Very short set-up times.
- Chuck body case-hardened up to 315 mm Ø.
- · Large aperture (dimension E!).
- · Safety peg for maximum operator safety.
- Base jaws compatible with chucks of the system "F" and system "Duro".
- · Flexible clamping of small and large components.
- High-precision clamping of very small internal Ø.

#### **Application:**

For spindle noses DIN 55027 with studs and collar nuts. The chuck is always fitted to the spindle nose directly without an intermediate flange.

#### Standard:

## DIN 702-3.

#### Material:

Entirely made of steel, suitable for high speeds (see table).

### Supplied with:

1 safety chuck key and 1 set fastening screws.
1 set scroll stepped jaws. **Optional extras: For spare and additional jaws** see No. 313200 – 313350.
Colour code for accessories: Schunk self-centring chucks and jaws
Clamping range with external hard top jaws: 8 - 208 mm
Clamping range with internal hard top jaws: 72 - 224 mm
Clamping stroke per jaw S: 7 mm
External Ø A: 206 mm
Aperture E: 52 mm
Centring taper Ø B: 82.575 mm

## **Technical description**

| maximum speed                              | 4800 rpm                             |
|--|--------------------------------------|
| Centring taper Ø B                         | 82.575 mm                            |
| Short taper arbor                          | 5                                    |
| Size of studs                              | M10                                  |
| Clamping stroke per jaw S                  | 7 mm                                 |
| Aperture E                                 | 52 mm                                |
| Clamping range with external hard top jaws | 8 - 208 mm                           |
| Number of studs                            | 4                                    |
| Clamping range with internal hard top jaws | 72 - 224 mm                          |
| External Ø A                               | 206 mm                               |
| Туре                                       | 200                                  |
| Weight                                     | 18.6 kg                              |
| Chuck key hexagon socket K                 | 12 mm                                |
| Series                                     | ROTA-S plus                          |
| Standard                                   | DIN 702-3                            |
| Colour code for accessories                | Schunk self-centring chucks and jaws |
| Type of product                            | Self-centring chucks                 |

## Accessories

| Base jaw set, 3 pieces, angled serrations for chuck type 200 | 313200 200 |
|--|------------|
| Base jaw set, 3 pieces, straight teeth for chuck type 200    | 313207 200 |
| Hardened top jaw set, 3 pieces for chuck type 200            | 313250 200 |
| Base jaw set, 3 pieces, angled serrations for chuck type 200 | 313205 200 |
| Hardened top jaw set, 3 pieces for chuck type 200            | 313210 200 |