



## Jaw cutting attachment, Outer / inner Ø: 176/110 mm



### Order data

Order number	315900 176/110
GTIN	4019208059471
Item class	38L

### Description

#### Version:

Within the body is a **drop-forged gear scroll**, which is rotated via a knurl ring on the periphery of the body. This gear scroll moves 3 **reversible** adjustment jaws steplessly inwards or outwards. For turning, the clamping screws of the adjustment jaws are positioned in the bore of the lathe chuck top jaws and the chuck is tightened. **During turning the chuck is in the same condition (preloaded) as for the subsequent workpiece machining.**

#### Callout:

Adjustment jaws  
Knurl  
Housing with spiral ring  
Top jaws  
Insert screw

#### Application:

For precision machining **internal and external diameters of soft top jaws** on lathe chucks. **Also suitable for external and internal re-grinding** of hardened top jaws to **correct radial runout.**

Insert area Ø position J: 35 - 125 mm  
Insert area Ø position A: 170 - 260 mm  
Weight: 3.5 kg  
suitable for chucks up to Ø: 200 mm

## Technical description

Insert area Ø position J	35 - 125 mm
suitable for chucks up to Ø	200 mm
Weight	3.5 kg
External Ø	176 mm
Internal Ø	110 mm
Insert area Ø position A	170 - 260 mm