



Revolving lathe centre for interchangeable heads., Morse taper: 4



Order data

Order number	320659 4
GTIN	4045197774361
Item class	31Z

Description

Version:

- **Punch axis of through-hardened steel mounted on shank bearings.**
- **Live centre through hardened, multiple regrinding possible.**
- **Precision roller bearings for high concentricity.**
- **Maintenance-free due to lifetime lubrication.**
- **Special seal prevents ingress of dirt and coolant.**
- **Complete tool hardened and ground.**

Application:

For all types of lathe, equally suitable for roughing and finish turning.

Flexible application thanks to exchangeable inserts. For general use on turrets and counter-spindles on CNC machines.

Optional extras:

Exchangeable inserts No. 320625 - 320631

Note:

Changing the inserts in the key surfaces by counter-rotation.

Body Ø D: 76 mm

maximum radial run-out: 0.005 mm

maximum speed: 3200 rpm

for workpiece weight: 350 kg

Length 1: 58 mm

L₂: 13 mm

Technical description

maximum speed	3200 rpm
---------------	----------

Body Ø D	76 mm
for workpiece weight	350 kg
maximum radial run-out	0.005 mm
Morse taper	4
suitable for colour code	K18
Length 1	58 mm
L ₂	13 mm
External Ø D ₁	18 mm
Shank Ø D ₂	32 mm
Type of product	Centring drill

Accessories

Insert for the revolving lathe centre Type 5	320629 5
Insert for the revolving lathe centre Type 4	320629 4
Insert for the revolving lathe centre Type 1	320629 1
Insert for the revolving lathe centre Type 3	320629 3
Insert for the revolving lathe centre Type 2	320629 2
Insert for the revolving lathe centre Type 6	320629 6