



Revolving lathe centre 60°, Morse taper: 3



Order data

| | |
|--------------|---------------|
| Order number | 321255 3 |
| GTIN | 4045197774415 |
| Item class | 31Z |

Description

Version:

Point angle 60°.

- **With extended centre and draw-off nut, specially for CNC machines.**
- **Complete tool hardened and ground.**
- **Special roller bearings for high loads and speeds.**
- **Live centre through hardened, can be reground many times.**
- **Maintenance-free due to lifetime lubrication.**
- **Special seal prevents ingress of dirt and coolant.**

Application:

For high loads and speeds, specially for NC machines.

Note:

Draw-off nut for NC machines to remove tip from tailstock sleeve.

Body Ø D: 52 mm

Reach B: 94 mm

largest centre point Ø 60° A: 25 mm

maximum radial run-out: 0.003 mm

Centre point length C: 30 mm

maximum speed: 12000 rpm

Technical description

| | |
|------------------------|----------|
| Body Ø D | 52 mm |
| Centre point length C | 30 mm |
| maximum radial run-out | 0.003 mm |

| | |
|--|----------------|
| maximum speed | 12000 rpm |
| largest centre point \varnothing 60° A | 25 mm |
| Reach B | 94 mm |
| for workpiece weight | 600 kg |
| Morse taper | 3 |
| Type of product | Centring drill |