

# Fixed solid carbide lathe centre 60°, very large Ø / Morse taper: 50/4



## **Order data**

Order number	323200 50/4
GTIN	4045197882479
Item class	31Z

# **Description**

#### **Version:**

- · High-precision solid carbide tip. Close-fitting carbide design for optimum stability and freedom from breakage, no additional safety equipment required.
- · Tip angle 60°.
- · High surface quality on the shank for optimum fit.
- · Complete tool hardened and ground.
- · With carbide tips for applications with high wear.

#### **Description:**

Lathe centres are mainly used on lathes to support long and slim workpieces, since with these workpieces there would otherwise be a risk of the workpiece bending or moving around as a result of the forces generated.

The lathe centre is secured with a Morse taper. The workpiece is clamped in the chuck and a counterbore is added using a centre drill. After re-clamping, the lathe centre is then inserted.

## **Application:**

For grinding high-precision components.

#### **Optional extras:**

Draw-off nut No. 323230.

## Note:

Order the draw-off nut separately. Geometric dimensions to DIN 806 E.

Head length L: 57.5 mm External Ø D: 50 mm

Ø d: 35 mm

maximum radial run-out: 0.001 mm

# **Technical description**

External Ø D	50 mm
Morse taper	4
Ød	35 mm
maximum radial run-out	0.001 mm
Head length L	57.5 mm
Type of product	Centring drill