



## Marker L



### Order data

Order number	358752
GTIN	4020772550226
Item class	38D

### Description

#### Version:

Body of aluminium with Weldon shank. Stepless adjustment of the pre-load force. Character depth 0.1 - 0.3 mm.

#### Advantage:

Surface sealing without weakening or damaging the material. Inscription speed corresponds to the maximum feed rate. High wear resistance, with long working life for the special needles. Suitable for inscriptions on round surfaces. Can be used on the lathe. High process reliability. Needles easily withdrawn, therefore **quick needle change**. Irregularities up to 7 mm in the workpiece surface (depending on profile) can be compensated.

#### Application:

For marking on a wide variety of materials such as aluminium, titanium, steel, bronze, copper, brass, plastics etc. Smaller needle tips allow inscriptions on harder surfaces up to 57 HRC.

#### Note:

Order marking needle No. 358755; 358756 **separately**.

L<sub>1</sub>: 119 mm

L: 108 mm

Ø D<sub>1</sub>: 3 mm

Shank Ø d: 20 mm

Ø D: 42 mm

### Technical description

Ø D	42 mm
L <sub>1</sub>	119 mm
L	108 mm

Shank $\varnothing$ d	20 mm
$\varnothing$ D <sub>1</sub>	3 mm
Type	1560ML