

Garant
Neutral centring vice, Jaw width A: 120 mm

Order data

Order number	360133 120
GTIN	4045197801906
Item class	310

Description
Version:

Centring vice for flexible applications.

- **Absolute operational reliability thanks to enclosure.**
- **High repetition accuracy 0.02 mm.**
- **Variable central alignment ± 0.02 mm.**
- **User-friendly design, versatile range of jaws.**
- **Functional faces hardened.**
- **Sturdy design of tool steel, surface protection by brief exposure nitriding.**

Advantage:

- **Flexible lightweight.**
- **Multi-functional use.**

Directly on the machine bed, exchange pallets or extension base (360156).

Application:

Ideal for 5-face machining, perfect for clamping blank parts. Extremely versatile, wide range of applications: Pallet and automated systems, multiple clamping for instance on clamping rails, individual clamping on extension bases or directly on the machine.

Supplied with:

2 table clamps. Socket insert No. 642700 E12.

Optional extras:

For clamping jaw variants see No. 360135 to 360148.

Clamping force up to maximum: 25.5 kN

Torque: 60 Nm

Weight: 5.1 kg
 Stroke: 25 mm
 Jaw width A: 120 mm
 Length: 130 mm

Technical description

Stroke	25 mm
Width	120 mm
Torque	60 Nm
Clamping force up to maximum	25.5 kN
Height	51 mm
Length	130 mm
Weight	5.1 kg
Jaw width A	120 mm
Type of product	Machine vice

Accessories

Pair of gripp top jaws for type 120	360141 120
Pair of soft top jaws for type 120	360145 120
Pair of carbide top jaws for type 120	360138 120
Pair of soft top jaws for type 120	360146 120
Pair of carbide top jaws for type 120	360135 120
Pair of carbide top jaws for type 120	360137 120
Pair of gripp top jaws for type 120	360140 120
Pair of Vee jaws for type 120	360148 120
Pair of gripp top jaws for type 120	360142 120
Pair of gripp top jaws for type 120	360143 120
Pair of carbide top jaws for type 120	360136 120