



NC8 NC high pressure vice, Type: 125MX



Order data

Order number	360405 125MX
GTIN	2050002046979
Item class	34A

Description

Version:

Compact size: Optimum ratio between clamping range and overall length. The clamping force can be pre-set **without using tools: in 11 steps:** Jaw width 90 mm, **in 4 steps:** Jaw width 125 / 160 / 200 mm. Particularly rigid base body of GJS-60, **top and bottom faces ground; pairing accuracy 0.02 mm.**

Feature:

Fully enclosed low-maintenance nitrided spindle!

- **Increased service reliability.**
- **Optimised swarf protection.**
- **Minimised cleaning requirement.**

With 25H6 M10 holes at 200 mm pitch for zero-point clamping system.

Application:

Can be used horizontally or laterally, **since the side faces are ground to an accuracy of -0.05 mm.**

Supplied with:

2 stepped jaws (= standard!), 1 crank handle, 4 table clamps.

Optional extras:

Clamping stud No. 360025 - 25 M10.

Front jaws 361140 – 361150.

Note:

- **Dimensions of the NC 8 are identical to the Allmatic TC / LC.**
- **Jaws interface compatible with TC / LC.**
- **NC 8 (No. 360405) supersedes the products LC (No. 360500) and TC (No. 360400).**
- **TC / LC are no longer available!**

· **Sizes 125 MX and 125 LX are supplied with jaws 361295 125 and 361296 125.**

Version: Zero-point clamping system

Clamping force up to maximum: 40 kN

Weight: 35 kg

Overall length L: 483 mm

Base body length a: 398 mm

Tenon width $B_1 -0.05$: 126 mm

Clamping range b: 0 - 182 mm

Technical description

Jaw height h	39.5 mm
Type	125
Clamping range d	131 - 313 mm
$r \pm 0.015$	118 mm
Clamping force up to maximum	40 kN
Colour code for suitable accessories	NC8
Longitudinal slot l H7	20 mm
Clamping range b	0 - 182 mm
Base body length a	398 mm
Version	Zero-point clamping system
Overall length L	483 mm
Base body height c -0.02	100 mm
m	180 mm
Cross-slot n H7	20 mm
t	144 mm
Weight	35 kg
Tenon width $B_1 -0.05$	126 mm
Number of threads for workpiece back-stop	4
Series	NC8
Type of product	Machine vice

Accessories

Thread wiper set Type 125

360822 125