



Sliding clamps short, Type: 6



Order data

Order number	370092 6
GTIN	4020772003142
Item class	35A

Description

Version:

- Clamping force 30 or 49 kN with tightening torque of approx. 100 Nm.
- Forged clamping element of alloy heat-treatable steel, black galvanised.
- Steplessly adjustable height and length.
- Low installed height.

Supplied with:

- Base element and carrier.
- T-nut DIN 508 with T-bolt strength class 12.9.

Optional extras:

Pressure pieces No. 370096.

T-slot width: 18 mm

Fastening screw G: M16

Clamping height h-H: 6 - 50 mm

Clamping force: 40 kN

A: 42 mm

A₁: 92 mm

Technical description

A ₁	92 mm
L	110 mm
Fastening screw G ₁	M20
B	60 mm
Width across flats AF	10 mm
Clamping force	40 kN
B ₁	20 mm
T-slot width	18 mm
Adjustment travel V	15 - 95 mm
Clamping height h-H	6 - 50 mm
Fastening screw G	M16
A	42 mm
Type	764Md
Type of product	Sliding clamp

Accessories

Pressure pad, stainless steel Type DG	370096 DG
Spacer element short for type 6	370094 6
Pressure pad, stainless steel Type DR	370096 DR