



## Tapered clamp with adjusting support screw, Slot width a: 12 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 370680 12     |
| GTIN         | 4020772070274 |
| Item class   | 35A           |

### Description

#### Version:

Clamp painted. Clamping height steplessly adjustable via screw (without clamping lever).

#### Material:

Quenched and tempered steel, screw strength 8.8 or 10.9 (depending on size).

#### Supplied with:

Adjusting screw and T-bolt DIN 787 (No. 375300).

#### Note:

Click-on clamping lever, see No. 37 0750.

Clamping height h: 10 - 40 mm

Tee bolt DIN 787, No. 375300: Size 1212100

Length L: 100 mm

Width B: 40 mm

Height H: 20 mm

Distance from tip to slot: 21 mm

### Technical description

|              |       |
|--------------|-------|
| Slot width a | 12 mm |
|--------------|-------|

|                              |              |
|------------------------------|--------------|
| Slot length f                | 40 mm        |
| Distance from tip to slot    | 21 mm        |
| Tee bolt DIN 787, No. 375300 | Size 1212100 |
| Clamping height h            | 10 - 40 mm   |
| Length L                     | 100 mm       |
| Width B                      | 40 mm        |
| Height H                     | 20 mm        |
| Type                         | 6314V        |
| Type of product              | Plain clamp  |

---

## Accessories

|                                       |           |
|---------------------------------------|-----------|
| Detent clamp lever Slot width a 12 mm | 370750 12 |
|---------------------------------------|-----------|