



## Tapered clamp with adjusting support screw offset, Slot width a: 12 mm



### Order data

Order number	370685 12
GTIN	4020772074593
Item class	35A

### Description

**Version:**

Quenched and tempered steel, painted, screw strength 8.8.

**Application:**

To achieve the **lowest clamping height, turn the clamp around.**

**Supplied with:**

Adjusting screw and T-bolt DIN 787 (No. 375300).

**Note:**

Click-on clamping lever, see No. 37 0750.

Clamping height h: 10 - 48 mm

Tee bolt DIN 787, No. 375300: Size 1212100

Length L: 100 mm

Width B: 40 mm

Height H: 20 mm

Shoulder height A<sub>1</sub>: 8 mm

### Technical description

Distance from tip to slot	21 mm
---------------------------	-------

Shoulder height A <sub>1</sub>	8 mm
Shoulder depth A <sub>2</sub>	10 mm
Slot width a	12 mm
Tee bolt DIN 787, No. 375300	Size 1212100
Slot length f	40 mm
Clamping height h	10 - 48 mm
Length L	100 mm
Width B	40 mm
Height H	20 mm
Type	6314AV
Type of product	Plain clamp

---

## Accessories

Detent clamp lever Slot width a 12 mm	370750 12
---------------------------------------	-----------