



## Tapered clamp with adjusting support screw offset, Slot width a: 16 mm



### Order data

Order number	370685 16
GTIN	4020772074630
Item class	35A

### Description

#### Version:

Quenched and tempered steel, painted, screw strength 8.8.

#### Application:

To achieve the **lowest clamping height, turn the clamp around.**

#### Supplied with:

Adjusting screw and T-bolt DIN 787 (No. 375300).

#### Note:

Click-on clamping lever, see No. 37 0750.

Clamping height h: 13 - 58 mm

Tee bolt DIN 787, No. 375300: Size 1616125

Length L: 125 mm

Width B: 50 mm

Height H: 25 mm

Shoulder height A<sub>1</sub>: 10 mm

### Technical description

Distance from tip to slot	26 mm
---------------------------	-------

Shoulder height A <sub>1</sub>	10 mm
Tee bolt DIN 787, No. 375300	Size 1616125
Slot width a	16 mm
Shoulder depth A <sub>2</sub>	12.5 mm
Slot length f	45 mm
Clamping height h	13 - 58 mm
Length L	125 mm
Width B	50 mm
Height H	25 mm
Type	6314AV
Type of product	Plain clamp

---

## Accessories

Detent clamp lever Slot width a 16 mm	370750 16
---------------------------------------	-----------