



Horizontal toggle clamp with horizontal base, stainless, Type: 1



Order data

| | |
|--------------|---------------|
| Order number | 376620 1 |
| GTIN | 4020772008949 |
| Item class | 35A |

Description

Version:

Captive contact screws.

Compact design due to new handle.

Ergonomic 2-component handle, very comfortable to use due to enlarged hand rest.

With horizontal base for fixing to base plates etc.

Application:

For quick clamping and releasing of parts in series production or for installation as part of special clamping jigs. Suitable for clamping during drilling, reaming, grinding, bending, welding, fitting etc.

Hole spacing e: 13.7 mm

Hole spacing f: 19.7 mm

Bore \varnothing d: 5.2 mm

Clamping height L_2 : 19 mm

Clamping force P1: 800 N

Clamping force P2: 1100 N

Technical description

| | |
|----------------------|--------|
| Bore \varnothing d | 5.2 mm |
| overall height | 30 mm |
| overall length | 120 mm |

| | |
|--------------------------------|-------------|
| Clamping force P1 | 800 N |
| Contact screw | M5×30 mm |
| Clamping force P2 | 1100 N |
| Hole spacing e | 13.7 mm |
| Clamping height L ₂ | 19 mm |
| Hole spacing f | 19.7 mm |
| Type | 6830NIJ |
| Type of product | Quick clamp |