



Horizontal toggle clamp with safety-locking mechanism, Type: 4



Order data

| | |
|--------------|---------------|
| Order number | 376650 4 |
| GTIN | 4020772008826 |
| Item class | 35A |

Description

Version:

- Rivet made of stainless steel.
- Case-hardened bearing bushes.
- Bearings greased.
- Complete with hardened and galvanised contact screw.
- More compact design due to new handle.
- Ergonomic 2-component handle, very comfortable to use due to enlarged hand rest.
- Captive contact screws.

Application:

Particularly suitable for use where vibrations occur and for overhead applications due to patented safety-locking in closed and open state.

Hole spacing e: 41 mm

Hole spacing f: 36 mm

Bore \varnothing d: 8.5 mm

Clamping height L_2 : 45 mm

Clamping force P1: 2000 N

Clamping force P2: 3000 N

Technical description

| | |
|-------------------|--------|
| Hole spacing e | 41 mm |
| Clamping force P2 | 3000 N |

| | |
|--------------------------------|-------------|
| Hole spacing f | 36 mm |
| overall height | 75 mm |
| overall length | 287 mm |
| Clamping height L ₂ | 45 mm |
| Contact screw | M8×65 mm |
| Bore Ø d | 8.5 mm |
| Clamping force P1 | 2000 N |
| Type | 6830SJ |
| Type of product | Quick clamp |