



Push-pull toggle clamp short body, Type: 5



Order data

| | |
|--------------|---------------|
| Order number | 376700 5 |
| GTIN | 4020772008567 |
| Item class | 35A |

Description

Version:

Hardened shoulder screws.

- **Compact design due to new handle.**
- **Ergonomic 2-component handle, very comfortable to use due to enlarged hand rest.**

Application:

- **Direct fixing to sheet metal fixing points.**
- **Connected to jig body with threaded end of arm.**

Optional extras:

Angled base No. 376730.

Note:

- **Available in stainless steel on request.**

Clamping range: 67 mm

Clamping force P (pressure and traction): 4000 N

Overall height H: 149 mm

Overall length L: 364 mm

Contact screw: M12×50 mm

thread at front of clamp: M24×1,5 mm

Technical description

| | |
|--|-------------|
| Contact screw | M12×50 mm |
| thread at front of clamp | M24×1,5 mm |
| Clamping force P (pressure and traction) | 4000 N |
| Clamping range | 67 mm |
| Overall height H | 149 mm |
| Overall length L | 364 mm |
| Type | 6844J |
| Type of product | Quick clamp |

Accessories

| | |
|---------------------------|----------|
| Angled base sturdy Type 2 | 376730 2 |
| Angled base sturdy Type 5 | 376730 5 |
| Angled base sturdy Type 3 | 376730 3 |
| Angled base sturdy Type 1 | 376730 1 |
| Angled base sturdy Type 0 | 376730 0 |