



Push-pull toggle clamp with angled base, Type: 0



Order data

Order number	376710 0
GTIN	4020772008376
Item class	35A

Description

Version:

With **compound action**. Opening prevented by self-locking mechanism.

- **Rivet made of stainless steel, bearings greased.**
- **With long push-pull guide.**
- **Handle can be moved to any angle.**
- **With hardened and galvanised contact screw.**
- **Detachable angled base, permitting fixing to sheet metal walls.**

Application:

For use in special clamping fixtures for drilling, reaming, grinding, bending, welding, fitting etc.

Optional extras:

Angled base No. 376730.

Note:

- **Size 0 and 3 also available in stainless steel!**

Hole spacing f: 16 mm

Angled base width K: 25 mm

Clamping height b to centre of screw: 12 mm

Bore \varnothing d: 4.5 mm

Clamping range: 16 mm

Clamping force P (pressure and traction): 800 N

Technical description

Clamping force P (pressure and traction)	800 N
thread at front of clamp	M10x1 mm
Contact screw	M4x20 mm
Clamping range	16 mm
Clamping height b to centre of screw	12 mm
Bore Ø d	4.5 mm
Angled base width K	25 mm
Hole spacing f	16 mm
Overall height H	49.3 mm
Overall length L	140.5 mm
Type	6841J
Type of product	Quick clamp

Accessories

Angled base sturdy Type 2	376730 2
Angled base sturdy Type 3	376730 3
Angled base sturdy Type 5	376730 5
Angled base sturdy Type 0	376730 0
Angled base sturdy Type 1	376730 1