



Push-pull toggle clamp with angled base, Type: 1



Order data

| | |
|--------------|---------------|
| Order number | 376710 1 |
| GTIN | 4020772008406 |
| Item class | 35A |

Description

Version:

With **compound action**. Opening prevented by self-locking mechanism.

- **Rivet made of stainless steel, bearings greased.**
- **With long push-pull guide.**
- **Handle can be moved to any angle.**
- **With hardened and galvanised contact screw.**
- **Detachable angled base, permitting fixing to sheet metal walls.**

Application:

For use in special clamping fixtures for drilling, reaming, grinding, bending, welding, fitting etc.

Optional extras:

Angled base No. 376730.

Note:

- **Size 0 and 3 also available in stainless steel!**

Hole spacing f: 16 - 19.5 mm

Angled base width K: 30 mm

Clamping height b to centre of screw: 15 mm

Bore \varnothing d: 4.5 mm

Clamping range: 20 mm

Clamping force P (pressure and traction): 1000 N

Technical description

| | |
|--|--------------|
| Clamping height b to centre of screw | 15 mm |
| Bore Ø d | 4.5 mm |
| Clamping force P (pressure and traction) | 1000 N |
| Angled base width K | 30 mm |
| Contact screw | M4×20 mm |
| Hole spacing f | 16 - 19.5 mm |
| Clamping range | 20 mm |
| thread at front of clamp | M12×1,5 mm |
| Overall height H | 60.5 mm |
| Overall length L | 185 mm |
| Type | 6841J |
| Type of product | Quick clamp |

Accessories

| | |
|---------------------------|----------|
| Angled base sturdy Type 3 | 376730 3 |
| Angled base sturdy Type 1 | 376730 1 |
| Angled base sturdy Type 0 | 376730 0 |
| Angled base sturdy Type 2 | 376730 2 |
| Angled base sturdy Type 5 | 376730 5 |