



Heavy push-pull toggle clamp, Type: 5



Order data

Order number	376720 5
GTIN	4020772008581
Item class	35A

Description

Version:

- **Very sturdy design, with slide-ram guide.**
- **Slide-ram and hand lever move together.**
- **Body of malleable cast iron.**
- **Lever parts and slide ram made of quenched and tempered steel, galvanised and passivated.**
- **Hardened contact screw.**

Application:

- **For quick clamping / releasing in series production.**
- **As push or pull clamp.**
- **For incorporation within special jigs and fixtures.**
- **Suitable for clamping during drilling, reaming, grinding, bending, welding, fitting etc.**

Hole spacing g: 41 mm

Hole spacing e: 41 mm

Hole spacing f: 50 mm

Clamping height b to centre of screw: 38 mm

Bore \varnothing d: 8.5 mm

Clamping range: 40 mm

Technical description

Clamping height b to centre of screw	38 mm
Clamping range	40 mm
Hole spacing e	41 mm
Hole spacing g	41 mm
Hole spacing f	50 mm
Bore \varnothing d	8.5 mm
Clamping force P (pressure and traction)	10000 N
Contact screw	M12×50 mm
Overall height H	137.5 mm
Overall length L	380 mm
Type	6842
Type of product	Quick clamp