



## Heavy push-pull toggle clamp, Type: 7



### Order data

Order number	376720 7
GTIN	4020772008598
Item class	35A

### Description

#### Version:

- **Very sturdy design, with slide-ram guide.**
- **Slide-ram and hand lever move together.**
- **Body of malleable cast iron.**
- **Lever parts and slide ram made of quenched and tempered steel, galvanised and passivated.**
- **Hardened contact screw.**

#### Application:

- **For quick clamping / releasing in series production.**
- **As push or pull clamp.**
- **For incorporation within special jigs and fixtures.**
- **Suitable for clamping during drilling, reaming, grinding, bending, welding, fitting etc.**

Hole spacing g: 57 mm

Hole spacing e: 70 mm

Hole spacing f: 65 mm

Clamping height b to centre of screw: 55 mm

Bore Ø d: 11 mm

Clamping range: 50 mm

### Technical description

Clamping height b to centre of screw	55 mm
Hole spacing f	65 mm
Clamping range	50 mm
Hole spacing g	57 mm
Clamping force P (pressure and traction)	25000 N
Bore $\varnothing$ d	11 mm
Hole spacing e	70 mm
Contact screw	M12×50 mm
Overall height H	179 mm
Overall length L	460 mm
Type	6842
Type of product	Quick clamp