



Push-pull toggle clamp with hand lever (can be pulled-out), Type: 8



Order data

| | |
|--------------|---------------|
| Order number | 376760 8 |
| GTIN | 4020772092689 |
| Item class | 35A |

Description

Version:

- **Very sturdy design, with slide-ram guide.**
- **Slide-ram and hand lever move together.**
- **Body of malleable cast iron.**
- **Lever parts and slide ram made of quenched and tempered steel, galvanised and passivated.**
- **Hardened contact screw.**
- **Hardened bolts, maintenance-free sintered bushes.**
- **For high clamping forces.**
- **Body of malleable cast iron, burnished.**

Application:

- **For quick clamping / releasing in series production.**
- **As push or pull clamp.**
- **For incorporation within special jigs and fixtures.**
- **Suitable for clamping during drilling, reaming, grinding, bending, welding, fitting etc.**

Hole spacing k: 14.5 mm

Hole spacing l: 70 mm

Hole spacing m: 70 mm

Hole spacing g: 57 mm

Base body width n: 86 mm

Base body length f: 254 mm

Technical description

| | |
|--|-------------|
| Hole spacing k | 14.5 mm |
| Clamping range | 106 mm |
| Base body length f | 254 mm |
| Hole spacing l | 70 mm |
| Clamping height b to centre of screw | 28 mm |
| Clamping force P (pressure and traction) | 45000 N |
| Bore Ø d | 10.5 mm |
| Hole spacing g | 57 mm |
| Hole spacing m | 70 mm |
| Contact screw | M16×80 mm |
| Base body width n | 86 mm |
| Weight | 7.72 kg |
| Overall height H | 360 mm |
| Overall length L | 440 mm |
| Type | 6842PL |
| Type of product | Quick clamp |