



MaxX lifting magnet, maximum loading capacity (level): 125 kg



Order data

Order number	382001 125
GTIN	2050001944030
Item class	38D

Description

Version:

Compact robust design with neodymium permanent magnets. Stray magnetic flux is prevented by the "neutral crown" principle, thus preventing undesirable attraction forces acting on adjacent loads. The base body is made from a single block without any weld seams, thus ensuring constant capability. The lever has a lock which prevents accidental release of the load. Certified break-away force (see test certificate).

Application:

Quick and easy handling and transport of flat and round materials with 3-fold safety.

Note:

For the product dimensions, see the eShop. With rotating lifting eye.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 300 mm

maximum length flat: 1000 mm

minimum material wall thickness, flat: 20 mm

minimum material wall thickness, round: 10 mm

Dimension A: 69 mm

Dimension B: 118 mm

Technical description

minimum material wall thickness, flat	20 mm
Dimension D	79 mm
Dimension F	133 mm
Dimension A	69 mm
Dimension G	30 mm
Weight	3.5 kg
Dimension C	79 mm
Dimension B	118 mm
maximum Ø round	300 mm
minimum material wall thickness, round	10 mm
maximum lifting capacity flat	125 kg
Dimension E	66 mm
maximum lifting capacity round	50 kg
maximum length flat	1000 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet