



MaxX lifting magnet, maximum loading capacity (level): 1500 kg



Order data

Order number	382001 1500
GTIN	2050001944078
Item class	38D

Description

Version:

Compact robust design with neodymium permanent magnets. Stray magnetic flux is prevented by the "neutral crown" principle, thus preventing undesirable attraction forces acting on adjacent loads. The base body is made from a single block without any weld seams, thus ensuring constant capability. The lever has a lock which prevents accidental release of the load. Certified break-away force (see test certificate).

Application:

Quick and easy handling and transport of flat and round materials with 3-fold safety.

Note:

For the product dimensions, see the eShop.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 500 mm

maximum length flat: 3000 mm

minimum material wall thickness, flat: 45 mm

minimum material wall thickness, round: 30 mm

Dimension A: 316 mm

Dimension B: 383 mm

Technical description

minimum material wall thickness, round	30 mm
Weight	66 kg
maximum lifting capacity round	600 kg
Dimension E	122 mm
Dimension D	171 mm
Dimension C	166 mm
Dimension G	64 mm
Dimension B	383 mm
minimum material wall thickness, flat	45 mm
Dimension F	330 mm
maximum lifting capacity flat	1500 kg
Dimension A	316 mm
maximum Ø round	500 mm
maximum length flat	3000 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet