



MaxX lifting magnet, maximum loading capacity (level): 2000 kg



Order data

Order number	382001 2000
GTIN	2050001944085
Item class	38D

Description

Version:

Compact robust design with neodymium permanent magnets. Stray magnetic flux is prevented by the "neutral crown" principle, thus preventing undesirable attraction forces acting on adjacent loads. The base body is made from a single block without any weld seams, thus ensuring constant capability. The lever has a lock which prevents accidental release of the load. Certified break-away force (see test certificate).

Application:

Quick and easy handling and transport of flat and round materials with 3-fold safety.

Note:

For the product dimensions, see the eShop.
 Test certificate: Manufacturer's test certificate
 maximum \varnothing round: 600 mm
 maximum length flat: 3000 mm
 minimum material wall thickness, flat: 55 mm
 minimum material wall thickness, round: 35 mm
 Dimension A: 390 mm
 Dimension B: 457 mm

Technical description

maximum lifting capacity round	800 kg
--------------------------------	--------

Dimension E	122 mm
Dimension G	64 mm
Dimension A	390 mm
maximum lifting capacity flat	2000 kg
Weight	80 kg
minimum material wall thickness, flat	55 mm
Dimension F	330 mm
minimum material wall thickness, round	35 mm
maximum length flat	3000 mm
Dimension D	171 mm
maximum Ø round	600 mm
Dimension C	166 mm
Dimension B	457 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet