



## MaxX lifting magnet, maximum loading capacity (level): 250 kg



### Order data

Order number	382001 250
GTIN	2050001944047
Item class	38D

### Description

#### Version:

Compact robust design with neodymium permanent magnets. Stray magnetic flux is prevented by the "neutral crown" principle, thus preventing undesirable attraction forces acting on adjacent loads. The base body is made from a single block without any weld seams, thus ensuring constant capability. The lever has a lock which prevents accidental release of the load. Certified break-away force (see test certificate).

#### Application:

Quick and easy handling and transport of flat and round materials with 3-fold safety.

#### Note:

For the product dimensions, see the eShop.

Test certificate: Manufacturer's test certificate

maximum  $\varnothing$  round: 300 mm

maximum length flat: 1500 mm

minimum material wall thickness, flat: 20 mm

minimum material wall thickness, round: 10 mm

Dimension A: 143 mm

Dimension B: 189 mm

### Technical description

Dimension A	143 mm
-------------	--------

maximum lifting capacity round	100 kg
maximum Ø round	300 mm
Dimension E	63 mm
maximum length flat	1500 mm
maximum lifting capacity flat	250 kg
Weight	6 kg
Dimension C	79 mm
minimum material wall thickness, flat	20 mm
Dimension D	79 mm
Dimension G	35 mm
Dimension B	189 mm
minimum material wall thickness, round	10 mm
Dimension F	130 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet