Mitutoyo

Digital caliper IP67, Measuring range: 150 mm



Order data

Order number	412623 150
GTIN	4946368693927
Item class	44A

Description

Version:

Electronic caliper with absolute electronics and large easy-to-read display. Resistant to water, oil, and dust. Low energy consumption permits 18000 h continuous use on a single battery (size 300: 5000 h). The device is turned on automatically when it is moved and switches off automatically when not used for about 20 minutes.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size 357.

Packaging: sturdy box Standard: DIN 862 Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm Error limit: 0.03 mm Jaw length: 40 mm

Technical description

Calibration	A1
Depth gauge available	yes
Scale divisions	0.01 mm

Depth gauge	flat
Working time	15000 h
Error limit	0.03 mm
Standard	DIN 862
Jaw length	40 mm
Measuring range	0 - 150 mm
Auto switch-off	yes
Measured value saving	Once-off setting of the zero position
Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200

Accessories

Button cell / special battery Battery type 357	081560 357
Plastic case Type MS150	412470 MS150
Depth gauge holder, metal with 2 screws	412120
Plastic case Type MS150	412468 MS150