

**Mitutoyo**
**Digital caliper IP67 with data output, Measuring range: 150 mm**

**Order data**

Order number	412628 150
GTIN	4946368693941
Item class	44A

**Description**
**Version:**

Electronic caliper with absolute electronics and large easy-to-read display. Resistant to water, oil, and dust. Low energy consumption permits 18000 h continuous use on a single battery (size 300: 5000 h). The device is turned on automatically when it is moved and switches off automatically when not used for about 20 minutes.

**Function:**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

**Supplied with:**

1 battery No. 081560 size 357.

**Optional extras:**

Connecting cable (screw-on) No. 497085.

Packaging: sturdy box

Standard: DIN 862

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Error limit: 0.03 mm

Jaw length: 40 mm

**Technical description**

Measuring range	0 - 150 mm
-----------------	------------

Depth gauge	flat
Auto switch-off	yes
Error limit	0.03 mm
Scale divisions	0.01 mm
Jaw length	40 mm
Depth gauge available	yes
Working time	15000 h
Calibration	A1
Standard	DIN 862
Measured value saving	Once-off setting of the zero position
Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	Digimatic interface
Interface	USB interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

DAkKS calibration Calipers / depth gauges maximum measuring range 200 mm

021010 200

## Accessories

Receiver / USB keyboard interface Type	498965
Connecting cable with data switch Type D2	497085 D2
Plastic case Type MS150	412470 MS150
Connecting cable with data switch Type D1	497085 D1
Multi-receiver / USB keyboard interface Type	498975
Connecting cable with data switch Type USB2	497085 USB2
Plastic case Type MS150	412468 MS150
Transmitter Type S11E	498966 S11E
Button cell / special battery Battery type 357	081560 357
Depth gauge holder, metal with 2 screws	412120