

Mitutoyo
Digital caliper IP67 with data output, Measuring range: 200 mm

Order data

Order number	412628 200
GTIN	4946368694009
Item class	44A

Description
Version:

Electronic caliper with absolute electronics and large easy-to-read display. Resistant to water, oil, and dust. Low energy consumption permits 18000 h continuous use on a single battery (size 300: 5000 h). The device is turned on automatically when it is moved and switches off automatically when not used for about 20 minutes.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size 357.

Optional extras:

Connecting cable (screw-on) No. 497085.

Packaging: sturdy box

Standard: DIN 862

Depth gauge: flat

IP Index of Protection: IP 67

Measured value saving: Once-off setting of the zero position

Calibration: A1

Scale divisions: 0.01 mm

Error limit: 0.03 mm

Jaw length: 50 mm

Technical description

Standard	DIN 862
----------	---------

Working time	15000 h
Error limit	0.03 mm
Measuring range	0 - 200 mm
Jaw length	50 mm
Auto switch-off	yes
Scale divisions	0.01 mm
Depth gauge available	yes
Depth gauge	flat
Calibration	A1
Measured value saving	Once-off setting of the zero position
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 357
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	Digimatic interface
Interface	USB interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Labelling laser-etched Type	018940
Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200

Calibration Calipers / depth gauges maximum measuring range 200 mm

021000 200

Accessories

Connecting cable with data switch Type USB2

497085 USB2

Connecting cable with data switch Type D2

497085 D2

Depth gauge holder, metal with 2 screws

412120

Connecting cable with data switch Type D1

497085 D1

Button cell / special battery Battery type 357

081560 357

Receiver / USB keyboard interface Type

498965

Transmitter Type S11E

498966 S11E

Multi-receiver / USB keyboard interface Type

498975