

**Mitutoyo**
**Digital caliper with AOS system, Measuring range: 150 mm**

**Order data**

Order number	412632 150
GTIN	4946368667720
Item class	44A

**Description**
**Version:**

Measured result is displayed in easy-to-read characters (height 9 mm). The **AOS (Advanced Onsite Sensor)** electromagnetic measurement system offers enhanced protection against water and dust.

- **Absolute scale, no zeroing necessary, resulting in faster, more reliable measuring.**
- **Low power consumption (20,000 hours continuous use), battery charge indicator**

**Supplied with:**

1 battery No. 081560 size 357.

**Optional extras:**

Battery compartment cover No. 412239 size B.

Packaging: sturdy box

Standard: DIN 862

Depth gauge: flat

Calibration: A1

Scale divisions: 0.01 mm

Error limit: 0.03 mm

Jaw length: 40 mm

**Technical description**

Standard	DIN 862
Depth gauge	flat
Calibration	A1
Digit height LCD display	9 mm

Depth gauge available	yes
Working time	20000 h
Jaw length	40 mm
Scale divisions	0.01 mm
Error limit	0.03 mm
Measuring range	0 - 150 mm
Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
Power supply	Battery-powered
Measurement method of the measuring instrument	electro-magnetic inductive procedure
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200

## Accessories

Plastic case Type MS150	412470 MS150
Plastic case Type MS150	412468 MS150
Button cell / special battery Battery type 357	081560 357
Depth gauge holder, metal with 2 screws	412120