

**Mitutoyo**
**Digital caliper with AOS system and mm / inch selection, Measuring range: 150 mm**


## Order data

Order number	412639 150
GTIN	4946368667751
Item class	44A

## Description

### Version:

- **Absolute scale, no zeroing necessary, resulting in faster, more reliable measuring.**
- **Low power consumption (20000 hours continuous use), battery charge indicator.**

Measured result is displayed in easy-to-read characters (height 9 mm). The **AOS (Advanced Onsite Sensor)** electromagnetic measurement system offers enhanced protection against water and dust.

With mm / inch selection.

With **thumb roller**.

### Supplied with:

1 battery No. 081560 size 357.

### Optional extras:

Battery compartment cover No. 412239 size B.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

## Technical description

Article no of the battery / rechargeable battery fitted	081560 357
---	------------

Depth gauge	flat
Drive roller	yes
Reversible reading	mm / inch
Working time	20000 h
Standard	DIN 862
Measuring range	0 - 150 mm
Depth gauge available	yes
Scale divisions	0.01 mm
Error limit	0.03 mm
Jaw length	40 mm
Scale divisions	0.0005 inch
Number of batteries contained	1
Digit height LCD display	9 mm
Calibration	A1
Power supply	Battery-powered
Measurement method of the measuring instrument	electro-magnetic inductive procedure
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Labelling laser-etched Type	018940
Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

DAkKS calibration Calipers / depth gauges maximum  
measuring range 200 mm

021010 200

### Accessories

Depth gauge holder, metal with 2 screws

412120

Plastic case Type MS150

412468 MS150

Plastic case Type MS150

412470 MS150

Button cell / special battery Battery type 357

081560 357