

Mitutoyo
Digital caliper with AOS system and data output, Measuring range: 300 mm

Order data

Order number	412642 300
GTIN	4946368728384
Item class	44A

Description
Version:

Measured result is displayed in easy-to-read characters (height 9 mm). The **AOS (Advanced Onsite Sensor)** electromagnetic measurement system offers enhanced protection against water and dust.

- **Absolute scale, no zeroing necessary, resulting in faster, more reliable measuring.**
- **Low power consumption (20,000 hours continuous use), battery charge indicator**

Standard:

To manufacturer's standard

Supplied with:

1 battery No. 081560 size 357.

Optional extras:

Data cables No. 497080 and No. 497100 with data button.

Battery compartment cover No. 412239 size B.

Packaging: sturdy box

Standard: Manufacturer's standard

Depth gauge: flat

Calibration: A1

Scale divisions: 0.01 mm

Error limit: 0.04 mm

Jaw length: 64 mm

Technical description

Depth gauge available	yes
Jaw length	64 mm

Error limit	0.04 mm
Number of batteries contained	1
Measuring range	0 - 150 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Calibration	A1
Standard	Manufacturer's standard
Scale divisions	0.01 mm
Digit height LCD display	9 mm
Depth gauge	flat
Power supply	Battery-powered
Interface	USB interface
Interface	Digimatic interface
Measurement method of the measuring instrument	electro-magnetic inductive procedure
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 300 mm	011030 300
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300
Labelling laser-etched Type	018940