

## Digital caliper IP54 with data output, Measuring range: 300 mm



### **Order data**

Order number	412680 300
GTIN	4045197949363
Item class	41A

### **Description**

#### **Version:**

Digital calipers to IP54 with data output. Easy-to-read, high-contrast LCD display with 11.5 mm character height. Very long battery running time due to modern energy-efficient measurement system. The system switches automatically into power-saving mode after 20 minutes; moving the caliper reactivates it. There is no loss of the measurement value or zero point. With preset (dimension selection in advance). Ergonomic housing with easy-grip Haptoprene® component. The measuring faces are precision-lapped. without depth gauge. Advantage:

- · Ergonomic housing with easy-grip Santoprene® components.
- Long battery life.
- · Large high-contrast LCD display with 11.5 mm character height.
- · New modern design.

#### **Function:**

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

#### **Standard:**

to manufacturer's standard.

#### **Supplied with:**

1 battery No. 081560 size CR2032.

### **Optional extras:**

Data cable No. 498948, keyboard interface No. 498963

#### **Spare part:**

Data output cap No. 412237 size D, battery holder No. 412237 size B.

Packaging: sturdy box

Standard: Manufacturer's standard Reversible reading: mm / inch

IP Index of Protection: IP 54

Calibration: A1

Scale divisions: 0.01 mm Scale divisions: 0.0005 inch

Error limit: 0.04 mm Jaw length: 64 mm

# **Technical description**

Jaw length	64 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Error limit	0.04 mm
Calibration	<b>A</b> 1
Standard	Manufacturer's standard
Number of batteries contained	1
Scale divisions	0.0005 inch
Measuring range	0 - 300 mm
Reversible reading	mm / inch
Scale divisions	0.01 mm
IP Index of Protection	IP 54
Power supply	Battery-powered
Interface	RS232C interface
Interface	USB interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

# **Services**

Calibration Calipers / depth gauges maximum measuring
range 300 mm

011030 300

DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300
Labelling laser-etched Type	018940
Calibration Calipers / depth gauges maximum measuring range 300 mm	021000 300
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	021010 300

# **Accessories**

Connecting cable Type R2	498948 R2
Connecting cable Type USB2	498948 USB2
Plastic case Type MS300	412470 MS300
Button cell / special battery Battery type CR2032	081560 CR2032
Keyboard interface USB Type G2	498963 G2