


Garant**Digital caliper IP67 with data output, Measuring range: 150 mm****Order data**

| | |
|--------------|---------------|
| Order number | 412690 150 |
| GTIN | 4045197949387 |
| Item class | 41A |

Description**Version:**

Digital calipers to IP67 with data output. **Easy-to-read, high-contrast LCD display with 11.5mm character height.** Very long battery running time due to modern energy-efficient measurement system. The system switches automatically into power-saving mode after 20 minutes; moving the caliper reactivates it. There is no loss of the measurement value or zero point.

2-component body with **non-slip Santoprene® surface.** The calipers are resistant to water, coolant, oil, and dust – even when fitted with a data cable. The measuring faces are precision-lapped. With preset (dimension selection in advance).

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032.

Optional extras:

Data cable No. 498948, keyboard interface No. 498963.

Spare part:

Data output cap No. 412237 size D, battery holder No. 412237 size B.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

| | |
|---|--------------------------|
| Calibration | A1 |
| Scale divisions | 0.0005 inch |
| Measuring range | 0 - 150 mm |
| Error limit | 0.03 mm |
| Reversible reading | mm / inch |
| Jaw length | 40 mm |
| Scale divisions | 0.01 mm |
| Number of batteries contained | 1 |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032 |
| Depth gauge | flat |
| Standard | DIN 862 |
| IP Index of Protection | IP 67 |
| Power supply | Battery-powered |
| Interface | USB interface |
| Interface | RS232C interface |
| Measurement technology | digital |
| Material | Stainless steel, INOX |
| all parts | hardened |
| Packaging | sturdy box |
| Type of product | Vernier caliper standard |

Services

| | |
|--|------------|
| Calibration Calipers / depth gauges maximum measuring range 200 mm | 011030 200 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm | 011050 200 |
| Labelling laser-etched Type | 018940 |

Accessories

| | |
|---|---------------|
| Keyboard interface USB Type G2 | 498963 G2 |
| Button cell / special battery Battery type CR2032 | 081560 CR2032 |