



## Digital caliper IP67 with data output, Measuring range: 200 mm



### Order data

Order number	412690 200
GTIN	4045197949394
Item class	41A

### Description

#### Version:

Digital calipers to IP67 with data output. **Easy-to-read, high-contrast LCD display with 11.5mm character height.** Very long battery running time due to modern energy-efficient measurement system. The system switches automatically into power-saving mode after 20 minutes; moving the caliper reactivates it. There is no loss of the measurement value or zero point.

2-component body with **non-slip Santoprene® surface.** The calipers are resistant to water, coolant, oil, and dust – even when fitted with a data cable. The measuring faces are precision-lapped. With preset (dimension selection in advance).

#### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

1 battery No. 081560 size CR2032.

#### Optional extras:

Data cable No. 498948, keyboard interface No. 498963.

#### Spare part:

Data output cap No. 412237 size D, battery holder No. 412237 size B.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: flat

IP Index of Protection: IP 67

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 50 mm

## Technical description

Standard	DIN 862
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Scale divisions	0.01 mm
Calibration	A1
Reversible reading	mm / inch
Error limit	0.03 mm
Jaw length	50 mm
Depth gauge	flat
Scale divisions	0.0005 inch
Measuring range	0 - 200 mm
IP Index of Protection	IP 67
Power supply	Battery-powered
Interface	USB interface
Interface	RS232C interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

## Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Labelling laser-etched Type	018940

## Accessories

Keyboard interface USB Type G2

498963 G2