



Digital caliper with large display, Measuring range: 150 mm



Order data

Order number	412717 150
GTIN	4059192002107
Item class	43A

Description

Version:

Easy-to-read, high-contrast LCD display with 11 mm high characters. Modern energy-efficient measurement system, operational life approx. 3 years. The reference-lock function prevents measurement errors arising from accidentally touching the control buttons. Lapped slides, the measuring faces are precision lapped. With square depth gauge.

Supplied with:

1 battery No. 081560 size CR2032
 Packaging: sturdy box
 Standard: DIN 862
 Reversible reading: mm / inch
 Depth gauge: flat
 Measured value saving: MAHR reference-lock system
 Calibration: A1
 Scale divisions: 0.01 mm
 Scale divisions: 0.0005 inch
 Error limit: 0.03 mm
 Jaw length: 40 mm

Technical description

Jaw length	40 mm
Digit height LCD display	11 mm
Standard	DIN 862
Depth gauge available	yes

Calibration	A1
Working time	approx. 3 years
Reversible reading	mm / inch
Depth gauge	flat
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	MAHR reference-lock system
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200

Accessories

Button cell / special battery Battery type CR2032	081560 CR2032
Plastic case Type MS150	412468 MS150
Plastic case Type MS150	412470 MS150