

**Digital caliper with rod type depth gauge and data output, Measuring range: 150 mm****Order data**

Order number	412728 150
GTIN	4059192002121
Item class	43A

Description**Version:**

Easy-to-read, high-contrast LCD display with 8.5 mm high characters. Modern energy-efficient measurement system, operational life approx. 3 years. The reference-lock function prevents measurement errors arising from accidentally touching the control buttons. Lapped slides, the measuring faces are precision lapped.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Data cable No. 498940.

Packaging: sturdy box

Standard: DIN 862

Reversible reading: mm / inch

Depth gauge: \varnothing 1.5

Measured value saving: MAHR reference-lock system

Calibration: A1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.03 mm

Jaw length: 40 mm

Technical description

Standard	DIN 862
Digit height LCD display	8.5 mm
Calibration	A1
Depth gauge available	yes
Depth gauge	Ø 1.5
Jaw length	40 mm
Reversible reading	mm / inch
Working time	approx. 3 years
Scale divisions	0.01 mm
Scale divisions	0.0005 inch
Error limit	0.03 mm
Measuring range	0 - 150 mm
Measured value saving	MAHR reference-lock system
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Interface	RS232C interface
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Vernier caliper standard

Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
	011050 200

DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

Accessories

Plastic case Type MS150	412468 MS150
Receiver / USB keyboard interface Type	498965
Button cell / special battery Battery type CR2032	081560 CR2032
Connecting cable Type USB2	498940 USB2
Connecting cable Type R2	498940 R2
Plastic case Type MS150	412470 MS150
Multi-receiver / USB keyboard interface Type	498975
Transmitter Type S4E	498966 S4E
Connecting cable Type D2	498940 D2